AIR COMPRESSORS

2-Stage Compressors

30 Gallon

13 HP Horizontal with Honda Engine

SKU 344741 CPTRCP1330G 2,54999 • CFM: 25.3 @ 100 PSI

DELIVERY



Chicago Pneumatic **HONDA**

- Premium Cast Iron and Aluminum Hybrid Pump
- 12V Electric and Recoil Starter Standard
- EZ Pull Type Tank Drain
- Oil Monitor
- Cold Start Valve • Full 2 Year Warranty
- Pump Oil Included

Lift Gate Service SKU 361260 **125**00 CPTLIFTGATE

13 HP Horizontal with Honda Engine

SKU **110435** IRT2475F13GH **2**

Gas Powered Honda Engine

• CFM: 25 @ 175 PSI



(IR) Ingersoll Rand HONDA

Start-Up Kit SKU **970499** IRT32312936

• Includes: (2) Air Filter Elements, (2) Quarts 4-Cycle Engine Oil, (4) Liters of All Season Synthetic Lube

 Using this Kit Extends Compressor Pump Warranty to 2 Years

> **Lift Gate Service** SKU **262532 80**00 IRTLIFTGATE

13 HP Horizontal with Honda Engine

OEM Tank Color May Vary

Depending on Stock

SKU **110306** OEMTUK13030HGE



• Gas Powered Honda Engine

OEM TOOLS

• CFM: 22 @ 175 PSI • Cast Iron Pump

DELIVERY INCLUDED



Lift Gate Service SKU **295540 80**00 OEMLIFTGATE

2-Stage Compressors

60 Gallon





SKU **344627** CPTRCP561VNS

- CFM 15.3 @ 100 PSI
- Premium Cast Iron and Aluminum Hybrid Pump
- Volts: 208 230 Single Phase
- Magnetic Starter: Not Required
- Full 2 Year Warranty • Pump Oil Included

Lift Gate Service SKU **361260 125**00 CPTI IFTGATE

DELIVERY



Lift Gate Service SKU **262532 80**00 IRTI IFTGATE

80 Gallon

5 HP Vertical

Air Compressor SKU **210433** IRT2340L5

- CFM: 14.7 @ 175 PS
- Cast Iron Pump
- Volts: 230 Single Phase
- · Factory Mounted and Wired Motor

DELIVERY INCLUDED

Start Up Kit

SKU **970496** IRT32305880

• (4) Quarts Synthetic Lube and (2) Air Filters

• Use of Kit Extends **INCLUDED** Compressor Pump Warranty to 2 Years



OEM Tank Color May Vary

Depending on Stock

OEM TOOLS 5 HP Vertical Air Compressor with Magnetic Starter

SKU **110299** 0EMTE5060VM 1.0

- CFM: 15 @ 150 PSI
- Cast Iron Pump
- Volts: 230 Single Phase
- Factory Mounted and Wired Motor Starter
- Easy Access Drains



- · Vibration Damper Pads Synthetic Oil
- **Lift Gate Service**

SKU **295540 80**00 **OEMLIFTGATE**

5 HP Vertical

SKU **110300**

OEMTN5080VM

• Cast Iron Pump

Air Compressor



OEM TOOLS

2-Stage Compressors



SKU 344629 CPTRCP581V

- CFM: 18.5 @ 100 PSI
- Premium Cast Iron and Aluminum Hybrid Pump
- Volts: 208 230 Single Phase
- Premium Model Includes: Low Oil Level Switch, Auto Tank Drain, Triple Pass Pump Mounted Aftercooler
- Mag Starter Included
- Full 2 Year Warranty
- · Pump Oil Included

Lift Gate Service SKU 361260 12500 CPTLIFTGATE

7.5 HP Vertical Premium Model

SKU **344631** CPTRCP7581V

- CFM: 25.3 @ 100 PSI
- Premium Cast Iron and Aluminum Hybrid Pump
- Volts: 208-230 Single Phase
- Premium Model Includes: Low Oil Level Switch, Auto Tank Drain, Triple Pass Pump Mounted Aftercooler
- Mag Starter Included
- Full 2 Year Warranty
- Pump Oil Included

DELIVERY



Lift Gate Service SKU 262532 **80**00 **IRTLIFTGATE**



5 HP Vertical Air Compressor

SKU **095102** IRT2475N5V

- Cast Iron Pump
- CFM: 16.8 @ 175 PSI
- Volts: 230 Single Phase
- · Factory Mounted and Wired Motor

Start Up Kit

SKU **970496** IRT32305880

• (4) Quarts Synthetic Lube and (2) Air Filters • Use of Kit Extends Compressor Pump Warranty to 2 Years

7.5 HP Vertical Air Compressor

SKU 210434 IRT2475N7.5

- CFM: 24.0 @ 175 PSI
- Cast Iron Pump
- Volts: 230 Single Phase
- Factory Mounted and Wired Motor Starter

DELIVERY



OEM Tank Color May Vary Depending on Stock

• CFM: 16.5 @ 175 PSI • Volts: 230 Single Phase Factory Mounted and Wired Motor Starter • Easy Access Drains · Vibration Damper Pads · Low Oil Shut Off · Synthetic Oil

Lift Gate Service SKU **295540 80**00 OEMLIFTGATE

IN STOCK



OEMTUE7580VM

- CFM: 24.8 @ 175 PSI
- Cast Iron Pump
- Volts: 230 Single Phase
- Factory Mounted and Wired Motor Starter

• Easy Access Drains

- · Low Oil Shut Off
- · Vibration Damper Pads
- · Synthetic Oil



DELIVERY

OEM TOOLS

HONDA

2-Stage Compressors

10 HP Horizontal Air Compressor SKII 210437

IRT2545E10V

SKU **970497**

• CFM: 35 @ 175 PSI • Cast Iron Pump **INCLUDED**

• Volts: 230 Three Phase • Factory Mounted and Wired Motor Starter Start-Up Kit

IRT32305898 • (4) Quarts Synthetic Lube and (2) Air Filters Use of Kit Extends Compressor

Lift Gate Service SKU **262532 80**00 IRTLIFTGATE

Pump Warranty to 2 Years





AND SAVE

120 Gallon

10 HP Horizontal Air Compressor Three Phase

SKU**110305** OEMTUK100120M3 • CFM: 32.5 @ 175 PS

• Cast Iron Pump • Volts: 230 Three Phase • Factory Mounted and Wired Motor Starter



IN STOCK

OEM TOOLS

10 HP Horizontal **Air Compressor**

· Low Oil Shut-off

· Synthetic Oil

Auto Drain

Single Phase SKU 110303 **DELIVERY** OEMTUK100120M1 INCLUDED

> **Lift Gate Service** SKU **295540 80**00 OEMLIFTGATE

Gas Compressor

8 HP, 30 Gallon **Horizontal with Honda Engine**

SKU **979920** OEMTUE8030HGE

• CFM: 16 @ 175 PSI Cast Iron Pump • Synthetic Oil

• Electric Start

5.5 HP, 30 Gallon **Horizontal with Honda Engine**

SKU **110298** OEMPUK5530G

• Gas Powered Honda Engine • CFM: 12.0 @ 90 PSI

IN STOCK



Specifications Subject to Change Without Notice or Liability. | Customers Responsible for Offloading Equipment Upon Arrival.

Leasing Terms Available.

Leasing Terms Available!

Ask Your AutoZone® Commercial Sales Manager

See Page 84 for More Information

Tool & Equipment QUARTERLY


Air Compressors



MAXair PREMIUM 5 HP. 60 Gallon. Single Stage Compressor SKU **544555** MAXGNC5160V1M

• 18.5 CFM @ 100 PSI

- Max. Rated PSI: 170
- (Ships Preset to 150 PSI)
- Voltage: 208/230V Single Phase
- Rugged Cast Iron Cylinders Are Built to Work Hard and Last a Long Time
- · Extended Easy to Reach,
- No Mess Oil Drain





- 18.5 CFM @ 100 PSI • Max. Rated PSI: 170
- (Ships Preset to 150 PSI)
- Voltage: 208/230V Single Phase • Rugged Cast Iron Cylinders Are Built
- to Work Hard and Last a Long Time • Extended Easy to Reach, No Mess
- Oil Drain • 2 Year Warranty



7.5 HP. 80 Gallon. Single Stage Compressor SKU **544557 2,39999** MAXGNC71801MS

- Max. Rated PSI: 170 (Ships Preset to 150 PSI)
- Voltage: 208/230V Single Phase
- Rugged Cast Iron Cylinders are Built to Work Hard and Last a Long Time
- Extended Easy to Reach, No Mess Oil
- 2 Year Warranty
- Magnetic Starter Included

PREMIUM

PREMIUM Air Compressors*

- Rugged Cast Iron Cylinders Are Built to Work Hard and Last a Long Time
- Extended Easy to Reach, No Mess Oil Drain

18.5

CFM

- Max Rated PSI: 170 Ships Preset to 150 PSI (Unless Noted in Table)

SKU	Part #	Description	Specifications	Price
547023	MAXGNC4160V1M	5 HP, 60 Gallon, Single Stage	• 12.5 CFM @ 100 PSI • 208/230V Single Phase	1,049.99
547015	MAXGNC73801C2	7.5 HP, 80 Gallon, Single Stage	• 30 CFM @ 100 PSI • 208/230V 3 Phase	2,399.99
547016	MAXGNC73801C4	7.5 HP, 80 Gallon, Single Stage	• 30 CFM @ 100 PSI • 460V 3 Phase	2,399.99
547018	MAXGNC75801CS	7.5 HP, 80 Gallon, Single Stage	• 30 CFM @ 100 PSI • 575V 3 Phase	2,399.99
547019	MAXGNC101208M	10 HP, 120 Gallon, Single Stage	• 50 CFM @ 100 PSI • 208V Single Phase • Magnetic Starter	3,949.99
547020	MAXGNC103208M	10 HP, 120 Gallon, Single Stage	• 50 CFM @ 100 PSI • 208V 3 Phase • Magnetic Starter	3,699.99
547021	MAXGNC103230M	10 HP, 120 Gallon, Single Stage	• 50 CFM @ 100 PSI • 230V 3 Phase • Magnetic Starter	3,699.99
547022	MAXGNC103460M	10 HP, 120 Gallon, Single Stage	• 50 CFM @ 100 PSI • 460V 3 Phase • Magnetic Starter	3,699.99

Part #	Description	Specifications	Price
MAXGNC105575M	10 HP, 120 Gallon, Single Stage	• 50 CFM @ 100 PSI • 575V 3 Phase • Magnetic Starter	3,699.99
MAXGNC153208M	• 60 CFM @ 100 PSI • 208V 3 Phase • Max Rated PSI: 150 • Magnetic Starter		5,199.99
MAXGNC153230M	15 HP, 120 Gallon, Single Stage	60 CFM @ 100 PSI 230V 3 Phase Max Rated PSI: 150 Magnetic Starter	5,199.99
MAXGNC153460M	15 HP, 120 Gallon, Single Stage	60 CFM @ 100 PSI 460V 3 Phase Max Rated PSI: 150 Magnetic Starter	
MAXGNC155575M	15 HP, 120 Gallon, Single Stage	60 CFM @ 100 PSI 575V 3 Phase Max Rated PSI: 150 Magnetic Starter	5,199.99
	MAXGNC105575M MAXGNC153208M MAXGNC153230M MAXGNC153460M	MAXGNC105575M 10 HP, 120 Gallon, Single Stage MAXGNC153208M 15 HP, 120 Gallon, Single Stage MAXGNC153230M 15 HP, 120 Gallon, Single Stage MAXGNC153460M 15 HP, 120 Gallon, Single Stage	10 HP, 120 Gallon, Single Stage 50 CFM @ 100 PSI 575V 3 Phase Magnetic Starter 60 CFM @ 100 PSI 208V 3 Phase Magnetic Starter 60 CFM @ 100 PSI 208V 3 Phase Magnetic Starter 60 CFM @ 100 PSI 208V 3 Phase Magnetic Starter 60 CFM @ 100 PSI 208V 3 Phase Magnetic Starter 60 CFM @ 100 PSI 208V 3 Phase Magnetic Starter 60 CFM @ 100 PSI 230V 3 Phase Magnetic Starter 60 CFM @ 100 PSI 246V 3 Phase Magnetic Starter 60 CFM @ 100 PSI 460V 3 Phase Magnetic Starter 60 CFM @ 100 PSI 450V 3 Phase Magnetic Starter 60 CFM @ 100 PSI 575V 3 Phase Magnetic Starte

SKU **295540** OEMLIFTGATE **80**00

Regulators/Filters/Drains

Air Compressors Are Horizontal Tank Units

Air Compressor with Honda Engine and Electric Start SKU **544558** MAXGN1130TRHM Z

11 HP, 30 Gallon Truck Mount

- 18.5 CFM @ 100 PSI
- Max. Rated PSI: 170 (Ships Preset to 150 PSI)
- 11-HP Honda GX340 Manual/Electric Start Engine - CARB Approved
- Extended Easy to Reach, No Mess Oil Drain
- Uses 12 Volt, Motorcycle-Style Starter Battery (Battery Not Included; Must Be Purchased



PREMIUM

18 HP, 55 Gallon Truck Mount **Vanguard V-Twin Electric Start** Air Compressor

SKU **544559** MAXGN1855TRHM

• 55 CFM @ 100 PSI

- Max. Rated PSI: 170 (Ships Preset to 150 PSI)
- 18HP Briggs and Stratton Vanguard Engine
- 2 Year Warranty



CARB Compliant

Single Stage Compressors

Single Stage, 6 HP* COMMONDES **60 Gallon Vertical Compressor** SKU 110297 OEMPK7060VS

- 99999 • 3 Cylinder Cast Iron Pump
- 19.5 CFM @ 90 PSI
- Max PSI: 150 • 230 Volt/Single Phase *3 HP/6 HP Peak



 Vibration Damper Pads, Synthetic Oil. Easy Tank Drain **OEM Tank Color May Vary Depending on Stock**



Single Stage, 5 HP*, 20 Gallon **Vertical Compressor**

Lift Gate

SKU **295540** OEMLIFTGATE


Service

8000

эки **110315** PUMPK5020VP **529**99



• CFM: 5.5 @ 90 PSI





Single Stage 6 HP*, 60 Gallon **Vertical Compressor**

SKU **436011** PUMPK6060V **59999**

- 2 Cylinder Cast Iron Pump • 12 CFM @ 90 PSI

Compressor/Generator/Welder







SKU **410033**

MTMAGWSR143M

• Electric Start Option Included

Maximum Rated Regulator)

• Battery and Cables Not Included

• Welder: 150A @ 100% Duty Cycle (50 - 170A Working Range)

Compressor Oil SAE30 (1 Qt) SKU **301791** PUM074-SAE30 1999

Compressor/Generator/Welder

• Quality Cast Iron Two Stage Compressor

Generator Output: 4 500 Watts Continuous

• CFM: 15.7 @ 175 PSI (Equipped with 150 PSI



Compressor Synthetic Oil (1 Ot) SKU **301795**

PUM074-SYN30

7099










Mi-T-M



• Adjustment Range is 5-125 PSIG Rated for 100 SCFM





without Shutting Down Air Line 3 Position Adjustment Knob

Lubricator May Be Filled





ARR5804

• Automatically Drains Compressor Tanks, Receiver Tanks or Filters

Oil Removing Filter (1/2")

Coalescing Filter

SKU **543081 999**

• .003 Micron Filter Element



• 6' Power Cord





Regulator with Gauge (1/4")

• Ensures Accurate and Consistent Air Pressure

for Spray Guns and Other Air Operating Tools

SKU **543086** ARRR262G

Digital Air Regulator

SKU 978113 7 999

25862



In-Line Air Tool Filter (1/4") SKU **543067**







SKU **543077** ARRDFD-10

• Maximum Flow Capacity: 15 CFM • Maximum Pressure: 125 PSI • See-Through Housing Shows Desiccant

Color Change, Indicates that the Dryer Needs to Be Replaced



ARRF354

Description















Modular Combo (3/8)
5 Stage Desico

ARRC7612XL • Includes Gauge, Shut-Off Valve and One Gallon of Desiccant

• Lowers the Dew Point to -30° F



Leasing Terms Available.



Free Delivery!

Specifications Subject to Change Without Notice or Liability. | Customers Responsible for Offloading Equipment Upon Arrival.

ARRF554AW



• Operating Pressure Range 5-125 PSI

• 40 Micron Element

• 3 Position Non-Rising Adjustment Knob







Integral Filter/Regulator w/Gauge (3/8") 543070 ARRB7536 99.99











Description	SKU	Part #	Price
Replacement Desiccant Silica Gel, 1 Quart	543068	ARR34189	16.99

Prices Subject To Change Without Notice. Please do not return purchases to the store. For information regarding warranty or repair and/or any questions or concerns, please call 1-877-298-6651.

AIR TOOLS

11 Piece, 1/2" Drive Deep Impact Socket Set (SAE) and 10 Piece, 1/2" Drive Deep Impact Socket Set (Metric) SKU **391196** | Part# 25594 (SAE) + SKU **391194** | Part# 25592 (Metric)

VALUE: \$109.98

1/2" Drive Composite Impact Wrench

1/2" Drive Composite Impact Wrench SKU **347258** | 24400

- Max. Torque: 900 Ft/Lbs.
- Air Consumption: 5.1 CFM
- Air Inlet Thread: 3/8" • Weight: 4.58 Lbs.
- Noise Power: 96.2 db.A

Offer Good Through March 31, 2016 - While Supplies Last



OEM TOOLS

1/2" Impact

Stubby 1/2" Drive Impact Wrench

SKU **626146** 24403

- Max. Torque: 450 Ft/Lbs. Reverse
- Small but Powerful
- Lightweight: 3.5 Lbs.
- 3 Torque Adjustments

Every Day Low Price



OEM TOOLS

• Max. Torque: 500 Ft/Lbs.

3/4" Heavy Duty **Impact Wrench**

3/4" Impact Wrenches

OEM TOOLS

• CFM: 3.9

SKU **466617** 25810

1/2" Impact Wrenches

OEM TOOLS

(IR) Ingersoll Rand



• 6,500 RPM Forward

OEM TOOLS



- 25774 • Torque: 400 Ft/Lbs.
- 5.6 CFM Air Consumption

OEM TOOLS

OEM



- Torque: 425 Ft/Lbs.
- 4 CFM Air Consumption



OEM TOOLS

(IR) togersoli Rand.

(III) logersoli Rand.

3/4" Impact Wrench SKU **970473** IRTIR261

• Torque: 1,300 Ft/Lbs.

569⁹⁹

• Jumbo Hammer Mechanism • Torque: 1,100 Ft/Lbs.

Mighty Compact 3/8"

Drive Impact Wrench

• Fits in One Hand (5-1/4 Inch in Length)

SKU **802213 1 4 999**

· Lightweight and Compact,

• Air Consumption: 4.7 CFM • Free Speed: 11.000 RPM

• Working Torque: 280 Ft/Lbs. • Maximum Torque: 320 Ft/Lbs. Reverse

• Clutch Type: Twin Hammer

3/8" Impact Wrench SKU **970486 10099**

• Most Powerful 3/8" Pistol

Only Weighs 3.5 Lbs.

24411

IRTIR212

Grip Impact

• Torque: 180 Ft/Lbs.

3/8" Titanium

• Torque: 300 Ft/Lbs.

Forward/Reverse

Air Impact Wrench

• Feather Touch Trigger and

Patented Push Button

SKU **198065 34999** IRT2115TIMAX

• Single Hammer Design

3/8" Impact Wrenches

(IR) Ingersoll Rand LOWER PRICE 1/2" Impact Wrench Classic

SKU **495316 1099** IRT231C

• Torque: 600 Ft/Lbs.

1/2" Quiet

Impact Wrench

SKU **738489** IRT2135QXPA **279**

• Twin Hammer Mechanism

• Weighs Only 4 Lbs.

• Torque: 780 Ft/Lbs.

• Light, Quiet and Powerful Impact

Pressure-Feed Lubrication

IR) Ingersoll Rand.

(R) Ingersoll Rand



- Pressure Fed Lubrication System
- Handle Exhaust Direct Away from User
- Standard of the Industry for 3 Decades • Sound Pressure: 94 - 105

1/2" Super Air **Impact Wrench with** 2" Extended Anvil

SKU **604744 22999** IRT231HA2

• Torque: 590 Ft/Lbs.

(IR) Ingersoll Rand

(IR) Ingersoll Rand.



Impact Wrench SKU **695134**

IRT2235TIMAX

• 1350 Foot Pounds of Torque

- 930 Foot Pounds of Reverse Torque
- Twin Hammer Impact Mechanism
- Lightweight

1" Impact Wrenches





1/2" Street Legal

"Thundergun"

• Torque: 625 Ft/Lbs.

Best-in-Class

Impact Wrench

SKU **495318 309 99** IRT232TGSL



• 10,000 RPM for Lightning Fast Removal Is

IRTIR285B6 66999 • 6" Anvil for Better Truck Wheel Nut

1" Impact Wrench with

- 1,770 Ft/Lbs. of Reverse Torque
- Hi-Efficiency Motor



1" Super Duty Impact with Extended Anvil

SKU **466618** 25811





Reversible Drills OEM TOOLS 3/8"

Reversible **Air Drill** SKU **466595** 25765

- 90 PSI
 - 4 CFM Air Consumption
 - 2,200 RPM Free Speed
 - 35 In/Lbs. Max Torque

 - Sound Level: 91 Decibels • Weight: 2-1/2 Lbs.

(IR) Ingersoll Rand. 3/8" Reversible



• Variable Speed Throttle Reversible Motor with a

- Quick Reverse Lever • 2.000 RPM Free Speed
- Lightweight, Compact



(IR) Ingersoll Rand.

- Heavy Duty 1/2" Industrial Grade

Air Hammers



• 2,200 Impacts Per Minute

- Recommended Air Pressure: 90 PSI
- Air Consumption: 6.3 CFM
- Air Inlet Thread Size: 1/4" NPT

Included

O≡M TOOLS



Tool & Equipment QUARTERLY

Air Sanders and Polishers

*While Supplies

Last



High Speed Air Sander

SKU 466594 **3999** 25764

• 90 PSI

- 4.5 CFM Air Consumption • 14,00 RPM Free Speed
- Sound Level 88 Decibels



6" Dual Action Sander

SKU 970475 **70**99 IRTIR311A

- Dual Action Pad Motion Reduces Swirl
- Built in Silencer for Quiet Operation



Dual Action Air Sander SKU **011577 1099**

33625830

- Air Consumption: 4.0 CFM
- Free Speed: 10,000 RPM
- Pad Size: 6"
- Recommended Air Pressure: 90 PSI Recommended Hose Size: 3/8"

Straight Line Sander

• Twin Piston Design for Smooth

• 3,000 Strokes Per Minute

• Quick-Action Paper Clamps

• Weight: 3.87 Lbs.

SKU **970479**

IRTIR315

Operation



Prep Tool

SKU **094650 1 999** 25778

Orbital Sander

• 8,000 RPM Free Speed

• One Hand Operation

• Contoured Palm Grip

SKU **970476**

IRTIR312A

- RPM: 20,000
- Quick Change"Twist Lock" Mandrel

2" Surface

All Twist Lock Accessories Work with this Sander

(IR) Ingersoil Rand

- 4 Position Air Volume Control
- CFM: 3

SKU **347259 17 99** • Maximum Torque: 75 Ft/Lbs. **Impact** • Air Inlet: 1/4" NPT • Free Speed: 450 RPM

12 Piece, 3/8" Drive Shallow Impact Socket Sets

SKU **391191** | Part# 25589 (SAE) + SKU **391190** | Part# 25587 (Metric) **VALUE: \$48.98**

• Air Consumption: 2.52 CFM • Ratchet Pawl: Single · Exhaust: Rear

Mechanism **Adds Power** and Prevents Kickhack

Offer Good Through March 31, 2016 - While Supplies Last



3/8" Drive Reactionless Air Ratchet

SKU 347259 | Part# 24401

1/4" Air Ratchets 1/4" Industrial

24401

Air Ratchet SKU **466593 1 999** 25763

• Delivers 25 Ft/Lbs. of Torque and 265 RPM Free Speed

1/4" Stubby

SKU **970472** IRT105D2

• Delivers 25 Ft/Lbs. of Torque and



250 RPM Free Speed



Heavy-Duty Angle Sander SKU **970477** IRTIR313A

• 5,000 RPM Free Speed

- Lightweight, Only 4-1/2 Lbs.
- Ball Bearing Construction for Long Life



Heavy-Duty Buffer Polisher

SKU 970478 🦱 IRTIR314A

- Hi-Speed Range: 1,500-2,500 RPM
- 7" Backing Pad
- Handles the Toughest Polishing and Buffing Jobs



Die Grinders

1/4" Mini Angle Air **Die Grinder**

SKU 802214 6 4 99 Recommended Air Pressure: 90 PSI

- Air Consumption: 2.8 CFM
- Free Speed: 18,000 RPM
- Air Inlet Thread Size: 1/4" NPT

Body

• Angle: 90 Degrees



1/4" Extended Air **Die Grinder**

SKU 802216 6 4 99 24408

- Recommended Air Pressure: 90 PSI
- Air Consumption: 2.5 CFM
- Free Speed: 23,000 RPM
- Air Inlet Thread Size: 1/4" NPT

Body



Air Tire **Buffer**

SKU **802218**

- Air Consumption: 3.5 CFM
- Free Speed: 2,600 RPM
- Minimum Hose Size: 3/8



Composite

1/4" Mini Angle Die Grinder and Surface **Prep Kit**

sku **094648 5 999**

- Right Angle Design for Tight Places
- Weight Only 1.1 Lbs. • Grinding and Cleaning
- All-in-One Kit • 20,000 RPM for Clean Precise Work
- 4 CFM Air Usage Works with Small Compressors • Adjustable Air Throttle for
- Control to Fit the Job
- Air Inlet Strainer Angle Head Grease Fitting

Includes: (10) Grinding Stones in 1/4" and 1/8" Shank Sizes; 1/4" and 1/8" Collet;

(4) 2" and (4) 3" Cleaning Discs Stripping; 2" and 3" Backing Pads; 2 Piece Hand Wrench and 2 Piece Disc



3" Mini Die Grinder SKU 466591 **199** 25761

- 4 CFM Air Consumption
- 25,000 RPM Free Speed
- Recommended Air Pressure: 90 PSI • Recommended Hose Size: 3/8"
- Air Inlet Thread Size: 1/4" NPT



1/4" Mini Air

Die Grinder

• Ultra Compact Size Fits into Spaces

47 hohesin

Regular Die Grinders Cannot

for Optimum Performance

• Free Speed: 25,000 RPM

Lightweight: 0.7 Lbs.

• Collet Size: 1/4"

• Requires Only 2.4 CFM @ 90 PSI

SKU **751631**

24404

• Recommended Air Pressure: 90 PSI

- Air Consumption: 3.4 CFM
- Air Inlet Thread Size:
- 1/4" NPT





- 6 CFM Air Consumption
- 25,000 RPM Free Speed
- Recommended Air Pressure: 90 PSI
- Air Inlet Thread Size: 1/4" NPT

OEM TOOLS

- Recommended Air Pressure: 90 PSI
- Air Inlet Thread Size: 1/4" NPT



1/4" Compact Air Die Grinder SKU 802211 799

- 24405 • Recommended Air Pressure: 90 PSI
- Air Consumption: 3.4 CFM
- Free Speed: 25,000 RPM
- Air Inlet Thread Size:
 1/4" NPT

1/4" Air Die Grinder SKU **802212** / 099 24406

- Free Speed: 22,000 RPM



SKU **466592** 25762

• Recommended Hose Size: 3/8"



3/8" Air Ratchets

3/8" Pro Air Ratchet

SKU 210212 🥖 25819

• Max Torque: 60 Ft/Lbs. • Free Speed: 160 RPM

3/8" Air Ratchet

• Recommended Air Pressure: 90 PSI

- SKU **970485 11999** IRTIR107XPA
- Advanced Head Design • Features 54 Ft/Lbs. of Torque • 360° Adjustable Exhaust



SKU 495290 1999 • Torque: 76 Ft/Lbs.

• Variable Speed Button Trigger

• 360° Adjustable Exhaust



(IR) Ingersoll Rand

Cut Off Tools

Heavy Duty Air Nibbler SKU **970480**



• Starts Cuts in the Center of a Panel

• Holds 1/4" Radius Accurately

(IR) Ingersoll Rand. Air **Reciprocating Saw** SKU **970481**

- Designed for Cutting Intricate Shapes
- Cuts Flat and Curved Surfaces • Comes with (6) High Speed Steel

Cutting Blades



(IR) Ingersoll Rand **Heavy Duty Air Shear** SKU 970484 2 IRTIR7802SA

Heavy Duty OMM TOOLS Reciprocating Air Saw

· Shear that Cuts Squares,

• Cuts Up to 20 Gauge without Chips

Angles and Circles

SKU **802225** 24409

• Recommended Air Pressure: 90 PSI • Air Consumption: 1.7 CFM

• Enhanced Blade Guard Design and Trigger Safety Lock

• 9,000 Strokes Per Minute

