





**Free Delivery!** 

Specifications Subject to Change Without Notice or Liability. Customers Responsible for Off-loading Equipment Upon Arrival.

Leasing Terms Available.

38

Prices Subject To Change Without Notice. Please do not return purchases to the store. For information regarding warranty or repair and/or any questions or concerns, please call 1-877-298-6651.

# Leasing Terms Available!<sup>†</sup>

Ask Your AutoZone<sup>®</sup> Commercial Sales Manager







Do Not Include Vehicles, Installation or Optional Equipment as Sho

S KESPONSIDIE TOF UTT-IOAQING EQ Ask Your Sales Rep for Details. Ask Your AutoZone<sup>®</sup> Commercial Sales Manager.

39

SKU **186464** 

• Pre-Assembled Lock Mechanism







40

Prices Subject To Change Without Notice. Please do not return purchases to the store. For information regarding warranty or repair and/or any questions or concerns, please call 1-877-298-6651.





- Ladder lock safety system with "auto engage" locking bar
- Extra-large slider blocks for added stability
- 10 Lock Positions
- Aircraft quality cables
- Single Point Lock Release
- 18" Wide non-skid, diamond plate runways
- · Casters, Jack Tray, and Approach Ramps included

## WHEEL SERVICE

# TC-530

Semi-Automatic 1,59

- Internal Clamping Capacity: 12" 23
- External Clamping Capacity: 12 23 Max Wheel Diameter: 38
- Wheel Width: 3" 12"
- Swing arm design
- Bead seating inflation jets are integrated in the clamping jaws
- Side mounted Bead Breaker



1,69999 TC-950 Semi-Automatic **Tire Changer** 

**2,699**99 TC-950-WPA High Performance Tire Changer with Press Arm

 Internal Clamping Capacity: 15" - 28'
 External Clamping Capacity: 13" -24' Max Wheel Diameter: 47"
 Wheel Width: 3" - 15" Swing arm design Bead seating inflation jets are integrated in the clamping jaws Twin clamping cylinders provide

- more power to hold the most difficult rims Conveniently located and powerful bead breaker
- Large diameter hex mount/demount shaft for extra rigidity
- Left side press arm (WPA)
- Ideal for low profile tires (WPA)
- No scratching, machine never contacts rim (WPA)



 Three centering cones · Speed nut and caliper standard

#### **WB-953 High Performance** Wheel Balancer

 Max Wheel Diameter: 39' • Rim Width: 1.5" - 20" • Rim Diameter: 10" - 24" Rim Diameter: 10" - 24"
 And caliper come standard
 Optional motorcycle adapter Self-calibrating; Self-diagnosis Optimization program

> **WB-448** Heavy Duty Truck Wheel Balancer

Max Wheel Diameter: 47

- Rim Width: 1.5" 20" Rim Diameter: 10" 24"
- Wheel Weight Capacity: 298 lbs
   Self-calibrating; Self-diagnosis
- Pneumatic Wheel lift included
- Foot brake for manual stop
  Capable of balancing a full range of wheels Car and Truck cones come standard

1,249<sup>99</sup>

Static balancing

is available

2,49999



Prices Subject To Change Without Notice. Please do not return purchases to the store. For information regarding warranty or repair and/or any questions or concerns, please call 1-877-298-6651.





# Leasing Terms Available!<sup>†</sup>

Ask Your AutoZone® **Commercial Sales Manager** 



### **CL10 Series Lifts**



#### **CL10 Versymmetric** 10,000 Lbs. 2 Post Lift SKU **298485** CHVCI 10V3

- Exclusive Versymmetric® Technology Provides a Versatile 2 Lifts In One<sup>™</sup> Design to Safely Lift Vehicles Symmetrically or Asymmetrically Within the Same Service Bay
- Standard Offset Arm Design Provides Directspot™ to Vehicle's Front Lifting Points for Built-In Productivity
- Double Telescoping Screw Pads Adjust from 4-7/8" to
- 6-3/8" Reducing the Need for Adapters Rubber Door Guards Protect Vehicles from Door Damage When Accessing Driver Controls
- 11' 8" Standard Height Allows Lift To Be Placed In Standard Service Bay with 12' Ceiling
- Heavy-Duty 5" Diameter Pulley and 5/16" Cable Reduces Stress On Equalization System and Increases Cable Life
- Available 2' and 3' Column Extensions Enable Technician to Work at an Ergonomic Height When Servicing Taller Vehicles



Industry First Two Post Lift with **directSPOT™** Offset 3 Stage Front Arms Plus 3 Stage Rear Arms for Single Sweep Spotting - Eliminates the Need of Rolling Vehicles Back and Forth to Swing Front Arm Clear of Front Tire

» Maximum Arm Sweep, Reach and Retraction Meets the Widest Range of Recommended Lifting Points

### **Express Service Lifts**



- 10,000 Lbs. 2 Post Dual **Pendant Controls Lift** SKU 851785
- Single Sweep Spotting No Rolling Vehicles Back and Forth to Swing Front Arm Clear of Front Tire
- Vehicle Spotting by Providing an Unobstructed View to Lifting Points



rice Does Not Include Vehicles, Installation or Ontional Equipment as Shown

#### CL10-XP9 9,000 Lb. **Dual Pendant Controls 2** Post Pad Lift SKU 851786 CHLCL10XP9DPC

- CL10-XP9 Two Post Pad Lifts Come Standard with (4) 1-1/2" and (4) 3" Rubber Spotting Blocks and (4) Two Position Adapter Blocks
- Dual Pendant Power Controls Expedites Vehicle Spotting by Providing an Unobstructed View to Lifting Points

**DESIGNED TO LIFT ALL OF TODAY'S LOWER PROFILE PERFORMANCE CARS AND SMALLER** FRAME CARS IN MIND.





**CL10 Versymmetric** 10,000 Lbs. 2 Post Dual **Pendant Controls Quick Cycle Lift** SKU 851780 CHLIOV3DPCQC 5,74

- Quick Cycle Technology: Increased Rise of Speed to 27 Seconds from 48 Seconds Equating to a 42% Time Savings. Lowering Speed is Held to a Constant 17 Seconds (Approximately) Regardless of the Weight of the Vehicle.
- Up/Down Power Button + Dual Single Point Technical Lock Release System Provides Lift Operation from Either Column



#### **CL10-XP9 9,000 Lbs. Quick** Cycle 2 Post Pad Lift SKU **851783** CHLCL10XP9QC

- CL10-XP9 Two Post Pad Lifts Come Standard with (4) 1-1/2" and (4) 3" Rubber Spotting Blocks and (4) Two Position Adapter Blocks
- Quick Cycle Technology Means 43% Faster Rise Time

Our Quick Vehicle Spotting Solution Is Perfect for Express Service Requirements Such As Quick Lube Applications, Tire Rotations, Tire Balancing, Brake Work, Inspection Check Lanes and Any Other General Service Need Where Productivity Is Essential






### SA10 10.000 Lbs. **2 Post Vehicle Lift** SKU 847098 CHLSA10

- Can be Configured in Either the Symmetric or Asymmetric Position
- 3 Stage Front Arms Provide Greater Overall Arm Sweep
- Double Telescoping Screw Pads to Minimize the Need for Adapters

Optional 2' Column Height Extensions Accommodate Higher Profile Vehicles. Includes (2) Height Extensions, Hose Extension Kit and New Cables.







Challenger Lifts' SA10 features the ability to be configured in either the symmetric or asymmetric position dependant upon the service requirements of your shop. The SA10 features 3 stage front arms that provide maximum extension and retraction ensuring safe and reliable lifting on all vehicles within rated capacity.

With adjustable height and width options, double telescoping screw pads, durable powder coat finish, plated arm restraints and pins and many other appealing features, the SA10 will accommodate the rigorous demands of a full service facility. Available in red and blue.