

Leasing Terms Available!†

Ask Your AutoZone®
Commercial Sales Manager

AutoZone®
Tool & Equipment QUARTERLY

How to Size Your Air Compressor

Determine Compressor Type:

- Single Tech Shop or Low Volume Usage: Single-Stage (90-125 PSI)
- Two or More Tech Shop or High Volume Usage: 2 Stage (125-175 PSI)

Determine Air Consumption. Conduct a Shop Audit on Air Requirements or Use These Benchmarks:

- 5 CFM per Person in General Repair Shop
- 8 CFM per Person in HD Truck Shop
- 12 CFM per Person in Paint and Body Shop

Make Adjustments to Above Total CFM Requirements to Compensate for Compressor Duty Cycle

- Multiply by 1.5 for Single Stage
- Multiply by 1.25 for 2 Stage
- Add 10% to Total for Air Leaks and Future Growth in Business

Chose a Compressor that Best Fits the Required CFM per PSI Rating

COMMON AIR TOOL CFM CONSUMPTION

AIR TOOL	CFM
Air Hammer	4.0
Body Polisher	2.0
Body Orbital Sander	5.0
Die Grinder	5.0
Drill, 1/16" to 3/8"	4.0
Grease Gun	3.0
Hydraulic Floor Jack	6.0

AIR TOOL	CFM
Impact Wrench 3/8"	2.0
Impact Wrench 1/2"=	3.5
Impact Wrench 3/4"	7.5
Impact Wrench, 1"	10
Medium Duty Sander	40.0
Spring Oiler	4.0
Touch-Up Paint Spray Gun	3.5

Gas Compressor

5.5 HP, 30 Gallon Horizontal with Honda Engine

SKU 110298
OEMPUK5530G **999⁹⁹**

- Gas Powered Honda Engine
- CFM: 12.0 @ 90 PSI
- ASME Certified



OEM TOOLS
HONDA

IN STOCK
Ready To Ship

8 HP, 30 Gallon Horizontal with Honda Engine

SKU 979920
OEMTUE8030HGE **1,799⁹⁹**

- Electric Start
- CFM: 16 @ 175 PSI
- Cast Iron Pump
- Synthetic Oil



Single Stage Compressors

Single Stage, 6 HP* 60 Gallon Vertical Compressor

SKU 110297
OEMPK7060VS **999⁹⁹**

- 3 Cylinder Cast Iron Pump
- 19.5 CFM @ 90 PSI
- Max. PSI: 150
- 230 Volt/Single Phase *3 HP/6 HP Peak

IN STOCK
Ready To Ship



Lift Gate Service
SKU 295540
OEMLIFTGATE
80⁰⁰

PLUS:
• Vibration Damper Pads, Synthetic Oil, Easy Tank Drain

OEM Tank Color May Vary Depending on Stock

Single Stage, 5 HP*, 20 Gallon Vertical Compressor

SKU 110315
PUMPK5020VP **529⁹⁹**

- CFM: 7.1 @ 40 PSI
- CFM: 5.5 @ 90 PSI
- 120/240 Volt / Single Phase *2 HP/5 HP Peak



Single Stage 6 HP*, 60 Gallon Vertical Compressor

SKU 436011
PUMPK6060V **599⁹⁹**

- 2 Cylinder Cast Iron Pump
- 12 CFM @ 90 PSI
- Max PSI: 150
- 230 Volt Single Phase *3 HP/6 HP Peak



Compressor Oil SAE30 (1 Qt)
SKU 301791
PUM074-SAE30 **19⁹⁹**



Compressor Synthetic Oil (1 Qt)
SKU 301795
PUM074-SYN30 **29⁹⁹**

Compressor/Generator/Welder

Compressor/Generator/Welder

SKU 410033
MTMAGWSR143M **4,674⁹⁹**

- Quality Cast Iron Two Stage Compressor
- Electric Start Option Included
- Battery and Cables Not Included
- Generator Output: 4,500 Watts Continuous
- Welder: 150A @ 100% Duty Cycle (50 - 170A Working Range)
- CFM: 15.7 @ 175 PSI (Equipped with 150 PSI Maximum Rated Regulator)



CARB Compliant

Regulators/Filters/Drains

Digital Air Regulator

SKU 978113
25862 **29⁹⁹**

- Ensures Accurate and Consistent Air Pressure for Spray Guns and Other Air Operating Tools



Regulator with Gauge (1/4")

SKU 543086
ARRR262G **24⁹⁹**

- Adjustment Range Is 5 - 125 PSIG
- Rated for 25 SCFM



In-Line Air Tool Filter (1/4")

SKU 543067
ARR9132 **14⁹⁹**

- Protect Your Air Tools
- Max Pressure: 500 PSI
- Length: 1-9/16"



Disposable In-Line Desiccant Filter Dryer (1/4")

SKU 543077
ARRDFD-10 **19⁹⁹**

- Maximum Flow Capacity: 15 CFM
- Maximum Pressure: 125 PSI
- See-Through Housing Shows Desiccant Color Change, Indicates that the Dryer Needs to Be Replaced



Particulate Filter (1/2")

SKU 543079
ARRF354 **34⁹⁹**

- 40 Micron
- 100 CFM
- 150 PSI



Description	SKU	Part #	Price
Particulate Filter (3/8")	543078	ARRF353	34.99

Air Regulator with Gauge (1/2")

SKU 543091
ARRR354G **44⁹⁹**

- Adjustment Range Is 5 - 125 PSIG
- Rated for 100 SCFM



Description	SKU	Part #	Price
Regulator with Gauge (3/8")	543088	ARRR353G	49.99

Automatic Lubricator (1/2")

SKU 543085
ARRL354 **59⁹⁹**

- Lubricator May Be Filled without Shutting Down Air Line
- 3 Position Adjustment Knob



Description	SKU	Part #	Price
Automatic Lubricator (3/8")	543083	ARRL353	59.99

Electronic Drain (1/2")

SKU 543065
ARR5804 **69⁹⁹**

- Automatically Drains Compressor Tanks, Receiver Tanks or Filters
- 110 Volt
- 6' Power Cord



Coalescing Filter Oil Removing Filter (1/2")

SKU 543081
ARRF554AW **69⁹⁹**

- .003 Micron Filter Element
- 37 CFM
- Manual Drain



Description	SKU	Part #	Price
Coalescing Oil Removing Filter (3/8")	543080	ARRF553AW	69.99

Integral Filter/Regulator with Gauge (1/2")

SKU 543071
ARRB754G **69⁹⁹**

- Operating Pressure Range 5 - 125 PSI
- 40 Micron Element
- 3 Position Non-Rising Adjustment Knob



Description	SKU	Part #	Price
Integral Filter/Regulator w/ Gauge (1/4")	543069	ARRB752G	69.99
Integral Filter/Regulator w/ Gauge (3/8")	543070	ARRB753G	69.99

Filter Regulator Lubricator w/Gauge Modular Combo (1/2")

SKU 543075
ARRC33354 **199⁹⁹**

Extend the Life of Your Air Tools!

- Cleans, Dries and Lubricates Air Supply
- Operating Pressure Range 5 - 125 PSI
- 40 Micron Element
- 142 CFM



Description	SKU	Part #	Price
Filter Regulator Lubricator w/ Gauge Modular Combo (1/4")	543072	ARRC33352	199.99
Filter Regulator Lubricator w/ Gauge Modular Combo (3/8")	543073	ARRC33353	199.99

5 Stage Desiccant Filter/Dryer

SKU 543076
ARRC7612XL **419⁹⁹**

- Includes Gauge, Shut-Off Valve and One Gallon of Desiccant
- Lowers the Dew Point to -30° F



Description	SKU	Part #	Price
Replacement Desiccant Silica Gel, 1 Quart	543068	ARR34189	14.99

Free Delivery!
in 48 Continental United States

Specifications Subject to Change Without Notice or Liability. Customers Responsible for Off-Loading Equipment Upon Arrival.

Leasing Terms Available.†
Ask Your Sales Rep for Details.

Leasing Terms Available.†
Ask Your AutoZone® Commercial Sales Manager.