SHOP EQUIPMENT TOOL & Equipment QUARTERLY









48" Stainless Steel Evaporative Cooler

sku **342430** PLC6622-3502 **3,799**

- Stainless Steel Housing, Large Wheels, Hinged Top Cover, Easy Access and Maintenance; Controls and Valves in Protected Location
- Cooling Area (est): 4000 Sq-Ft

14

36" Stainless Steel Evaporative Cooler SKU 342429 PLC6622-2502 **3,199**99

- Stainless Steel Housing, Large Wheels, Hinged Top Cover, Easy Access and Maintenance; Controls and Valves in Protected Location
- Cooling Area (est): 3000 Sq-Ft

Zone 11K, 36" Evaporative Cooler



- 36" Evaporative Cooler Provides Effective Spot Cooling That Normally Would Be Too Costly to Cool with Refrigerated Air
- Resin Housing, 38 Gallon Reservoir, Automatic Low Water Pump Shut-off and Integrated Touch Pad Interface with LED Indicators Cooling Area (est): 3000 Sq-Ft

Please do not return purchases to the store. For information regarding warranty or repair and/or any questions or concerns, please call 1-877-AZTOOL1.


SHOP EQUIPMENT





Crushproof 2.5"x 11' Flarelock Hose KII 977557

Crushproof 3" x 11" Flarelock Hose Crushproof 2.5"



- Exclusively for Cars and Small Trucks
- Each End is Flared to Permit Connection of Two or More Links at a Time

Crushproof 2.5" Y-Assembly Kit with F250 Adapter

SKU 977549 18499 ACSYA250 Designed for Converting Single Hose into Dual Exhaust System Vehicle Purposes

3" Y-Assembly Kit with F300 Adapter SKU 977550 ACSYA300 22499

SKU 977559 ACSFLT300 14999 Crushproof 3.5" x 11" Flarelock Hose SKU 977589 ACSFLT350 20499 Crushproof 4" x 11" Flarelock Hose

SKU 977590 ACSFLT400 24499

Crushproof Door Port for 2-1/2" Hose (Rubber)

SKU 977551 3999 ACSDF25

 Rubber Garage Door Port Adapter Designed for 2-1/2" ID



2-1/2" Crushproof **Bell Hose Adapter**



• Designed for Easy Adapting to All Sorts of Tailpipes

Connects with Ball and Snap





Service Station Kit SKU 977547 26999 ACSDSS25

 Includes: (2) Each - 4' x 2-1/2" Hoses (1) Each - 6' x 2-1/2" Hose (1) Each - 2-1/2" Rubber "Y" Connector (2) Each - Straight Tailpipe Adapter, Hook and Chain (1) Each - Splice Connector

Crushproof 3" Service Station Kit SKU 977548 ACSDSS30 32499

Crushproof 2.5" Straight Tailpipe Adapter with Hook and Chain







15



3" Straight Tailpipe Adapter with Hook and Chain	SKU 977539 ACSF300 39 99
3.5'' Straight Tailpipe Adapter with Hook and Chain.	SKU 977540 ACSF350 59 99
4" Straight Tailpipe Adapter with Hook and Chain	SKU 977541 ACSF400 74 99
3″ x 6″ Oval Tailpipe Adapter	SKU 977542 ACSF475 54 99
3.5" x 8.5" Oval Tailpipe Adapter	SKU 977543 ACSF575 64 99

Please do not return purchases to the store. For information regarding warranty or repair and/or any questions or concerns, please call 1-877-AZTOOL1.

PRESSURE WASHERS

Commercial - Job Site Pressure Washers



Under Pressure			
Pump			
 Brass and Stainless-Steel Unloader 			

Performance

- Built-In Low Pressure Detergent Injection
- Thermal Relief Valve Pump Protection
- In-Line Water Strainer

Engine

 Mi-T-M Series Engine with Low-Oil Shutdown • All Models are Carb Compliant in all Fifty States

Frame

- 1-Inch Powder Coated Steel Tube Handle
- Allows for Increased Portability
- Powder Coated Steel Base Plate Quick Release Gun/Wand Holder and Hose Wrap
- Pneumatic Tires with Solid Steel Axle Dual Rubber Isolators

Units Include:

- Quick Connect Nozzles (15°, 25° and Detergent Nozzle) • 25' x 3/8" Wire-Braided Pressure Hose
- (50' on MTMCM3501MMB and MTMCM401MMB Models)
- Professional-Grade Insulated Trigger Gun with Safety Lock-Off
- 36-Inch Lance with Rubber Grip

Direct Drive Axial Piston AR Pump



2700 PSI **Cold Water**

Per Week **Pressure Washer** SKU 409456 MTMCM270MLB

64900

 Direct Drive Crankshaft Mi-T-M Pump with Adjustable Pressure



Usage:

2-5 Hours



3900

 Direct Drive Crankshaft Mi-T-M Pump with Adjustable Pressure

Usage: 5-10 Hours 3500 PSI **Per Week Cold Water** Pressure Washer

SKU **409463** MTMCM3501MMB

,14900

• Direct Drive Crankshaft Mi-T-M Pump with Adjustable Pressure

Usage: 4000 PSI 5-10 Hours **Cold Water** Per Week **Pressure Washer** SKU **409464** МТМСМ401ММВ

1,199%

• Direct Drive Crankshaft Mi-T-M Pump with Adjustable Pressure

SKU	Part#	PSI	GPM	DISPLACEMENT/ENGINE
409456	MTMCM270MLB	2700	2.4	212cc Mi-T-M OHV
409457	MTMCM30MLB	3000	2.4	212cc Mi-T-M OHV
409463	MTMCM3501MMB	3500	2.8	280cc Mi-T-M OHV
409463	MTMCM401MMB	4000	3.4	420cc Mi-T-M OHV

Residential and Light Commercial



sku **410036** MTMCV240MMC **3999**9

 PSI: 2400 GPM: 2.0 Engine 170CC Mi-T-M OHV Includes: Professional Grade Trigger Gun, Two Piece Lance, 30' X 1/4" Nylon-Braided Pressure Hose and Quick Connect Nozzles (15, 25-Degree and Detergent Nozzle) Direct Drive Axial Piston AB Pump











GENERATORS

Maximum Output Under Any Given Situation. Durable and Reliable Featuring a Mi-T-M OHV Engine



Generator 3600 Watts



• Engine: 212CC Mi-T-M OHV with Low-Oil

- Shutdown Receptacles: (2) 120V, 20A GFCI Duplex and 120V, 30A Twist Lock
- Run Time: 8.5 Hours at Full Loac

We Carry the Full Line of Generac Generators*



GP3250 Portable Generator sku 973238 **479**99 GENGP3250

GP5000 Portable • Rated Watts: 5000 • Runtime at 1/2 Load: 10 Hours Generator

GENERAC

Free Delivery! • Rated Watts: 3250 • Runtime at 1/2 Load: 9.7 Hours • Outlets: (1) 120V 20A 5-20R Duplex Outlet; (1) 120/240V 20A

L14-20R Twist Lock Outlet Gas Tank: 3.5 Gallon

- Low-Oil Level Shutdown Automatically Safeguards Engine









Generator 6000 Watts ыли **409470** МТМGEN60MM0 **9999**99

- Rated AC Output: 5500 Watts
- Engine: 389CC Mi-T-M OHV with Low-Oil Shutdown
- Receptacles: (2) 120V, 20A GFCI Duplex and 120V, 30A Twist Lock/120V/240V, 30A Twist Lock
- Run Time: 6.5 Hours at Full Load





Generator **8000** Watts

SKU **409471** MTMGEN80MME

- Rated AC Output: 5500 Watts
- Engine: 420CC Mi-T-M OHV with Low-Oil Shutdown Electric Start (Battery Included
- Receptacles: (2) 120V, 20A GFCI Duplex and 120V, 30A Twist Lock/ 120V/240V, 30A Twist Lock
- Run Time: 6.0 Hours at Full Load

SKU 973239 GENGP5000

(1) Twistlock L14-30R Low-Oil Level Shutdown





- Rated Watts: 7000
- Runtime at 1/2 Load: 12 Hours
- Outlets: (2) 120V 20A GFCI 5-20R Duplex Outlets; (1) 120/240V 30A L14-30R Twist Lock Outlet

NEW

- Gas Tank: 9 Gallon
- Low-Oil Level Shutdown Automatically Safeguards Engine
- PowerBar™ Easily Monitors Power Being Consumed and Available



- Rated Watts: 8000 • Run Time at 1/2 Load: 10 Hours
- Outlets: (1) 120/240V 30A L14-30R Twist Lock Outlet; (2) 120V 20A GFCI 5-20R Duplex
- Includes: First Oil and Maintenance Kit

 Gas Tank: 9 Gallon Low-Oil Level Shutdown Automatically Safeguards Engine • PowerBar™ Easily Monitors Power Being Consumed and Available



*The Generac Generators Listed Above are Not for Sale in California

Prices Subject To Change Without Notice.

Please do not return purchases to the store. For information regarding warranty or repair and/or any questions or concerns, please call 1-877-AZTOOL1.



SKU 227560 WWSKC-5G

- Concentrated Floor Cleaning Solution Removing Grease and Grime from Shop Floors
- Mop and Bucket or Floor Scrubbing Machines
- Concentrated for Cost Effectiveness
- Safe on Sealed Floors

WWSHD-32CS

SKU 222846 WWSHD-1GCS

5 Gallon

SKU **227558**

WWSHD-5G

5 Gallon SKU 227559 WWSSU-5G

- Professional Wash Solution for Heated Spray Cabinet/Jet Cabinet Style Parts Washing Equipment
- Super Concentrated for Cost Effectiveness
- Quickly Blasts Away Grease, Oil, Carbon and Grime

Heavy-Duty Degreaser Concentrate

12 Spray Bottels (32 oz. Bottles) SKU **222841**

4 Gallons (4) 1 Gallon Jugs

Designed to Effectively Replace Hazardous Solvent in Water Based Parts Washers

Concentrated to Be Powerful and to Save You Money

Quickly Removes Grease, Oil, Carbon and Grime While Safe for the Technician and Your Parts



- Color Coordinated Sizes
- Quick and Simple to Shrink by Heat Gun

Sand Blasting

Abrasive Blast Cabinet (Bench Top) SKU **300119**

- 24815 • Easily Remove Paint, Rust and Oxidation
- Fits on Bench or Cabinet
- Dimensions H: 19.3"; W: 19.3"; Cubic Inches: 28.6"

Portable Blaster SKU 094831 **1099** DEEPB1

Ideally Suited for Small Abrasive Jobs. Simply Fill with Abrasive, Attach Your Air Hose and Begin Blasting.

- Sand Reservoir 4 Lbs Capacity
- Cast Aluminum Gun
- 70-110 PSI Operating Range



OEM



*While Supplies Last

17

Please do not return purchases to the store. For information regarding warranty or repair and/or any questions or concerns, please call 1-877-AZTOOL1.

Prices Subject To Change Without Notice.

SHOP EQUIPMENT Tool & Equipment QUARTERLY



Remember That Replacement is a Safety Issue.

As lift supports lose pressure over time, they will fail to support the weight of the hood, hatch or trunk. This situation will not improve, and failure to replace the lift support could cause serious injury.

MIGHTY LIFT!® GAS CHARGED LIFT SUPPORTS



- Coverage for almost all vehicle makes and models
- Universal coverage for RV, AG, marine, tool boxes and more...

Add on Sales! **Check Lift** Supports While **Performing Any Under Hood** Service

Replacement of a Pair of Lift Supports Takes **Only Minutes** to Perform!