# TIRE SERVICE







- Bead Loosening Power: 6,000 Lbs
- Maximum Wheel Width: 15"
- Maximum Outer Tire Diameter: 42"
- Power Requirements: 120V, 1Ph, 60Hz
- Maximum Wheel Width: 15 Maximum Outer Tire Diameter: 50" Power Requirements: 120V, 1Ph, 60Hz

NEW



- Maximum Wheel Width: 13" Maximum Outer Tire Diameter: 39"
- Power Requirements: 120V, 1Ph, 60Hz

NEW

• Maximum Wheel Width: 13" • Maximum Outer Tire Diameter: 40" • Power Requirements: 120V, 1Ph, 60Hz

**GEODYNA<sup>™</sup> 980L Truck** 

• Maximum Wheel Assembly Width: 25" (63.5 cm)

• Includes: Truck Centering Cones for Hub Piloted Wheels, and the Professional 4-Star/5-Star Centering

Arms for Stud Piloted Applications. As a Bonus, the

Geodyna 980L Comes with the Passenger/Light Truck

• Maximum Wheel Assembly Diameter: 8" - 30" (20.32

Wheel Balancer

 Wheel Weight: 500 Lbs (227 Kg) Balancing Modes: 10

Cycle Time: From 7 Seconds

Cones for Automotive Use

• Wheel Width: 2" - 20" (5cm - 50.8cm

SKU **467487** 

cm - 76.2)

HOFEEWB710BW

• Motor: 1 HP 115VAC





- - **INCLUDES**
  - PASSENGER AND LIGHT TRUCK CONES





# 201 Combination Brake Lathe, Single-speed

#### SKU **290004** 09999 HOF201TRUECUT 🚺

- Simple "One-Cut" Finish: Feed Carriage Speed is Factory Set for a "Like New" Micro-Finish
- Feed Carriage Speed May Be Set for One-Cut Finish for Very Fast Machining and High Production
- Fast Changeover of Tooling: Changeover from Disc Cutter to Drum Cutter is Achieved Quickly by Swiveling the Feed Carriage Assembly

Heavy-Duty Construction: From the Oversized Tapered Roller Bearings Supporting the Lathe Arbor to the 350 lbs Ductile Iron Chassis, the 201 Truecut Brake Lathe is Built for Years of Machining

#### **Tool Board for** 201 Brake Lathe SKU **290006**

HOFB203

201 Brake Lathe SKU **290008** HOFB206

Work Bench for





		SKU	Part#	Mount/Demount	Brand	Models
RED Nylon Mount/ Demount Head sku459185 2099 NEW	Coats Nylon Mount/Demount Head - Tapered Hole SKU459183 2099	459185	TMRTCR343	RED Nylon Head (Each)	Hunter Accuturn Ranger	TC250, TC300, TC325, TC350, TC2000, TC3250, TC3500, TC3000 andTC3100 Series (Require Adapter) 220A, All Other Models Require 102765 Adapter R980X Rev A Models, R980XR/NXT, R30XLT, RX-850/950-B Models, R23/23ST, R26ST/26EX, and R710 Models ONLY. Require RAN5150524 Adapter
	TMRTC183061 37-	459183	TMRTC183061	Nylon Head Kit with Tapered Hole *Use with Tapered Shaft 182767 or 182812	Coats Baseline	5030, 5040, 5050, 5060, 5065, 6050, 6060, 7050, 7055, 7060, 7065, 7655, 7660, 7665 BL200, BL300, BL400 and BL500
Nylon Mount/ Demount Head Kit with Round Hole skU 459187 TMRTC250309 9999 NEW	Coats Nylon Mount/Demount Head - Tapered Hole SkU 459189 TMRTC 450310 6999 NEW	459187	TMRTC250309	Nylon Head Kit with Round Hole	All Tool Coats Corghi Hofmann Sice	All Models RC1, 5, 10, 15, 20, Early 5060, 9010, 9024, APX90 All Rim Clamp Earlier Models Except 1550, 1620, 1625 M39, S40, S42, S43, S45, S408MAXI, S435, S436, S436TC
Nylon Mount/ Demount Head Kit with Round Hole sku 459195 TMRTC14024784	Coats Nylon Mount/Demount Head - Tapered Hole SKU 459174 TMRTC20024335	459189	TMRTC450310	Nylon Head with Round Hole Head Only	All Tool Coats Corghi Giuliano Hofmann Hunter Sice	All Models RC1, 5, 10, 15, 20, Early 5060, 9010, 9024, APX90 All Rim Clamp Shaft Needs to Be Turned 180 Degrees for This Head to Work Earlier Models Except 1550, 1620, 1625 Fits All TCX Series (Earlier TCX500 Requires Upgrade Shaft & Kit RP11-8-114-00091) M39, S40, S41, S42, S43, S45, S408MAXI, S435, S436, S436T0P
Mounting Flange for Demount Head (Flange Only)* SKU 899502 5 0 99 * Required on some		459195	TMRTC14024784	Nylon Head Kit	Accuturn Hofmann John Bean Snap On	3602, 3602HP, 4260, 4560MR, 4602, 5602, 5602 HP 1520, 1565, 1620, 1625EM, 3300, 3300EM, 1270, 2300, 3000, 3000GP EHP System IVE, IV, III, IIE All Models
RAN5150524 • Used on R980X Rev A Models, R980XR/NXT, R30XLT, RX-850/950-B Models, R23/23ST, R26ST/26EX, and R710 Models ONLY	<b>NEW</b> New Provide the switching from metal to nylon demount head	459174	TMRTC20024335	Nylon Head for TMRTC14024784 Head Kit Head Only	Accuturn Hofmann John Bean Snap On	3602, 3602HP, 4260, 4560MR, 4602, 5602, 5602 HP 1520, 1565, 1620, 1625EM, 3300, 3300EM, 1270, 2300, 3000, 3000GP EHP System IVE, IV, III, IIE All Models

11

# TIRE SERVICE

**User Setup Required** 

Partners Available

Service by Coats Service

## **Tire Changers**

# BASELINE 6-Month Parts Warranty **ENTRY LEVEL** TIRE CHANGERS

BaseLine is the Ideal Tire Changer for a Low Volume Shop that is Looking for a Durable, Entry-Level Changer to Change the Majority of OE Fitments.

- Includes Bead Sealing Jets to Aid in Inflation Access to Coats' Extensive Factory Authorized Service Network
- Assembled in the U.S.A.

# **BL200 Value Series Tire Changer** with 21" External Clamping



# Wheel Weights

# **Starter Kits** with Storage

## Bench Top Rack with 1,000 Coated Steel Weight Assortment

#### SKU **383181 QQ**99 AMM5202125

- Louvered Rack Can be Placed on Top of Any Workbench
- Includes: Steel Rack, Application Guide, Header Card, Bin Labels, Rim Gauge, Wheel Weight Hammer, 5 Styles Wheel Weights: PFE, ALFE, MCFE, TFE, FNFE, 40 Plastic Bins: 8 Each of Yellow, Grey, Black, Red and Orange

#### **Metal Floor Rack with** 1,700 Steel Wheel Weight Assortment



• Steel Rack, Application Chart, Header Card, Channel Cards, Rim Gauge, Premium Wheel Weight Hammer, Tape-A-Weight Scraper, 8 Styles of Wheel Weights: MCFE, ALFE, PFE, TFE, IWFE, FNFE, LHFE, INFE





Tape-A-Weight Steel Wheel Weights **Bulk Roll Replacement Parts** SKU 382953 AMM5528930025

• Includes Replenishment Box of 700 .25 Oz Segment Tape-A-Weight No Rack









Ask Your AutoZone® Commercial Specialist

**RED Nylon Mount/Demount Head** SKU 459185 3999 TMRTCR343



BASELINE

User Setup Required Service by Coats Service Partners Available

**BL225 ENTRY** LEVEL Wheel Balancer SKU 510978 AMM85002225 **999**99

 Includes 40mm Shaft, Wheel Calipers for Width Measurement, Durable Hub Nut, 3 Standard Cones (Optional Light Truck Cone Available), Premium Wheel Weight Hammer, Small Pressure Cup and Rubber Lip, Spring

12

**Got Questions?** Get Answers. Pricing, Specs, Repair or Warranty Info CALL TODAY 1-877-AZTOOL-1

**BaseLine Lift Gate Service** SKU 262529 AMMLIFTGATE 5500

Leasing Terms Available.

Weel Weight Frolie:	Wheel Weght Profile
FRFE 2000	(WFE Dire)
Wheel Weight Proble	Wheel Weight Profile
LHFE Start	MCFE Steel
Wheel Weight Proble:	Wheel Weglt Prolite
PFE Store	TFE Steel
	00000
Wheel Weglt Profile:	Wheel Weight Frolile

383102	AMM5530820045	FNFE,45g	59.99
383103	AMM5530820050	FNFE,50g	64.99
383105	AMM5530820055	FNFE,55g	64.99
383106	AMM5530820060	FNFE,60g	69.99
383107	AMM5530830010	ENFE,10g	34.99
383108	AMM5530830015	ENFE,15g	34.99
383109	AMM5530830020	ENFE,20g	39.99
383110	AMM5530830025	ENFE,25g	44.99
383111	AMM5530830030	ENFE,30g	49.99
383112	AMM5530830035	ENFE,35g	54.99
383113	AMM5530830040	ENFE,40g	59.99
383114	AMM5530830045	ENFE,45g	59.99
383115	AMM5530830050	ENFE,50g	64.99
383116	AMM5530830055	ENFE,55g	64.99
383117	AMM5530830060	ENFE,60g	69.99
383118	AMM5530850010	IWFE,10g	34.99
383119	AMM5530850015	IWFE,15g	34.99
383120	AMM5530850020	IWFE,20g	39.99
383121	AMM5530850025	IWFE,25g	44.99
383122	AMM5530850030	IWFE,30g	49.99
383123	AMM5530850035	IWFE,35g	54.99
383124	AMM5530850040	IWFE,40g	59.99
383125	AMM5530850045	IWFE,45g	59.99
383126	AMM5530850050	IWFE,50g	64.99
383127	AMM5530850055	IWFE,55g	64.99
383128	AMM5530850060	IWFE,60g	69.99

Prices Subject To Change Without Notice.

6-Month Parts

Warranty

Please do not return purchases to the store. For information regarding warranty or repair and/or any questions or concerns, please call 1-877-AZTOOL1.







- Reverse Spiral Flutes are Designed to Bite Down to Provide Maximum Gripping Power
- Universal Lobular Design Fits All Types of Fasteners
- For Use with 3/8" Square Drive Hand Ratchets, Impact Wrenches and Air Ratchets



# DID YOU KNOWE

## We Offer Specialty Wheel Service and Lift Equipment for Turf and Heavy Duty Applications

# Tire Test Tank

**Tire Tube** 

**Test Tank** 

LIS19822

SKU 291382 6999



#### The Tank Features Reinforcement Ribs for Extra Support • Will Handle Passenger Tire Sizes to Wide Oval and Light Duty Truck Tires

Dimensions 31" X 12" X 12"

### Blockhead Combo sku **409473 94999** BRA04-0168

- Includes the No-Mar Inflation Cage with our BlockHead Auto Inflator, Both of Which Can Handle Run-Flat and High Pressure Tires
- Max Tire Width: 21.5"
- Max Tire Diameter: 34"



### **Blockhead Automatic** Inflator

SKU **409472** BRA40-0075

- Auto Inflate/Deflate Nitrogen Conversion Ready
- Air Chuck and Fill Hose Included

Auto Inflation Made Affordable

# **Blockhead Cage Mounting Bracket** sku **410070 2999** BRA04-0143

• Bracket to Mount BlockHead to Tire Safety Cage

# **Tire Inflation Cage** SKU **410069 379**99 BRA03-0232

- No-Mar Coating-Protects Expensive Wheels
- Max Tire Width: 21.4"
- Max Tire Diameter: 34"

# SKU 394389 8999 KTL34645C Blue Cobra® Truck Tire Service Set 499 SKU **394447** KTL35442

**Classic Tubeless** 

**Truck Tire Iron** 

- Contains All the Tools You Need to Change Most 22.5" and 24.5" Tubeless Truck Tires Quickly And Easily
- Includes: 35440 Blue Cobra® Truck Tire Demount Tool, 34645C - T45AC Classicc Tubeless Tire Iron, 33050 - Double-End Tire Spoon, 35848 - 8 Lbs Bucket Euro Paste Lube, 30512 - Euro-Style Lube Applicator Brush, 31713 - Aluminum C-Lok™ Bead Holder, 31810 - Leather Rim Protector

Please do not return purchases to the store. For information regarding warranty or repair and/or any questions or concerns, please call 1-877-AZTOOL1.

